

# SAFETY DATA SHEET

## Graffiti Spray

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name                      Graffiti Spray

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses                      Graffiti Remover PC35 Washing and cleaning products

#### 1.3. Details of the supplier of the safety data sheet

Supplier                              Aztec Aerosols  
    Gateway  
    Crewe  
    Cheshire  
    CW1 6FA  
    T+44 (0) 1270 656380  
    F+44 (0) 1270 656381  
    info@aztecaerosols.com

#### 1.4. Emergency telephone number

Emergency telephone              +44 (0)7831 300868

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical hazards                      Aerosol 1 - H222, H229  
 Health hazards                        Eye Irrit. 2 - H319 STOT SE 3 - H336  
 Environmental hazards              Not Classified

**Human health**                        Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Environmental**                        This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment

**Physicochemical**                      Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

#### 2.2. Label elements

##### Pictogram



Signal word                              Danger

Hazard statements                      H222 Extremely flammable aerosol.  
    H229 Pressurised container: may burst if heated.  
    H319 Causes serious eye irritation.  
    H336 May cause drowsiness or dizziness.

## Graffiti Spray

<b>Precautionary statements</b>	P102 Keep out of reach of children. P260 Do not breathe vapour/ spray. P501 Dispose of contents/ container in accordance with local regulations.
<b>Contains</b>	1-METHOXY-2-PROPANOL, ALIPHATIC HYDROCARBON (D40)
<b>Detergent labelling</b>	≥ 30% aliphatic hydrocarbons, < 5% non-ionic surfactants
<b>Supplementary precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>1-METHOXY-2-PROPANOL</b>	<b>30-60%</b>
CAS number: 107-98-2	EC number: 203-539-1
	REACH registration number: 01-2119457435-35
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
STOT SE 3 - H336	
<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>	<b>10-30%</b>
CAS number: 68476-85-7	EC number: 270-704-2
<b>Classification</b>	
Flam. Gas 1 - H220	
Press. Gas (Liq.) - H280	
<b>ALIPHATIC HYDROCARBON (D40)</b>	<b>10-30%</b>
CAS number: —	EC number: 919-857-5
	REACH registration number: 01-2119463258-33-XXXX
<b>Classification</b>	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
<b>Dimethyl succinate</b>	<b>1-5%</b>
CAS number: 106-65-0	EC number: 203-419-9
	REACH registration number: 01-2119486681-29
<b>Classification</b>	
Eye Irrit. 2 - H319	

## Graffiti Spray

<b>Alcohol ethoxylate</b>	<b>1-5%</b>
CAS number: 68439-46-3	REACH registration number: N/A
<b>Classification</b>	
Acute Tox. 4 - H302	
Eye Dam. 1 - H318	

The full text for all hazard statements is displayed in Section 16.

**Ingredient notes** N-Methyl-2-Pyrrolidone (CAS 872-50-4; EC 212-828-1) : Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once.
<b>Inhalation</b>	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with foam, carbon dioxide, dry powder or water fog.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is highly flammable. Forms explosive mixtures with air.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Warn firefighters that aerosols are involved. Use water to keep fire exposed containers cool and disperse vapours.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

## Graffiti Spray

**Personal precautions** Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb spillage with non-combustible, absorbent material.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Do not spray on a naked flame or any incandescent material. Eliminate all sources of ignition.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### **1-METHOXY-2-PROPANOL**

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m<sup>3</sup>(Sk)

#### **PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

#### **ALIPHATIC HYDROCARBON (D40)**

Long-term exposure limit (8-hour TWA): SUP 1040 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits SUP = Supplier's recommendation.

### 1-METHOXY-2-PROPANOL (CAS: 107-98-2)

## Graffiti Spray

<b>DNEL</b>	Industry - Inhalation; Short term local effects: 553.5 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 369 mg/m <sup>3</sup> Industry - Inhalation; Long term systemic effects: 369 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 18.1 mg/kg/day Consumer - Inhalation; Long term systemic effects: 43.9 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 3.3 mg/kg/day
<b>PNEC</b>	- Fresh water; 10 mg/l - Marine water; 1 mg/l - STP; 100 mg/l - Sediment (Freshwater); 41.6 mg/kg - Sediment (Marinewater); 4.17 mg/l - Soil; 2.47 mg/kg - Intermittent release; 100 mg/l

### ALIPHATIC HYDROCARBON (D40)

<b>DNEL</b>	Workers - Dermal; Long term systemic effects: 300 mg/kg/day Workers - Inhalation; Long term systemic effects: 1500 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 300 mg/kg Consumer - Inhalation; Long term systemic effects: 900 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 300 mg/kg/day
-------------	---

## 8.2. Exposure controls

<b>Appropriate engineering controls</b>	Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.
<b>Personal protection</b>	Do not eat, drink or smoke when using this product.
<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
<b>Hand protection</b>	Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
<b>Hygiene measures</b>	Wash hands after handling. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn.

## **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	White/off-white.
<b>Odour</b>	Organic solvents.
<b>Flash point</b>	< -40°C
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.8% Upper flammable/explosive limit: 9.5%
<b>Auto-ignition temperature</b>	410-580°C

## Graffiti Spray

**Comments** Information given is applicable to the major ingredient.

### 9.2. Other information

**Other information** Not available.

**Volatile organic compound** This product contains a maximum VOC content of 788 g/l.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Stable at normal ambient temperatures and when used as recommended.

### 10.2. Chemical stability

**Stability** Avoid the following conditions:

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Does not decompose when used and stored as recommended.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** Keep away from oxidising materials, heat and flames.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**ATE oral (mg/kg)** 55,555.56

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 3,831.42

#### **General information**

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

#### **Inhalation**

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

#### **Ingestion**

Irritating. Symptoms following overexposure may include the following: Nausea, vomiting. Stomach pain.

#### **Skin contact**

Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

#### **Eye contact**

Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.

#### **Acute and chronic health hazards**

Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

## Graffiti Spray

<b>Route of exposure</b>	Inhalation
<b>Target organs</b>	Central nervous system Respiratory system, lungs
<b>Medical symptoms</b>	Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

### SECTION 12: Ecological Information

**Ecotoxicity** No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.

#### 12.1. Toxicity

**Toxicity** Not available.

#### 12.2. Persistence and degradability

**Persistence and degradability** Not available.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Not available.

#### 12.4. Mobility in soil

**Mobility** Not known.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** Not available.

#### 12.6. Other adverse effects

**Other adverse effects** Not available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

#### 14.1. UN number

<b>UN No. (ADR/RID)</b>	1950
<b>UN No. (IMDG)</b>	1950
<b>UN No. (ICAO)</b>	1950
<b>UN No. (ADN)</b>	1950

#### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	AEROSOLS
<b>Proper shipping name (IMDG)</b>	AEROSOLS
<b>Proper shipping name (ICAO)</b>	AEROSOLS

## Graffiti Spray

Proper shipping name (ADN) AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

### Transport labels



### 14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

Revision comments	Supplemental information added.
-------------------	---------------------------------



## Graffiti Spray

<b>Revision date</b>	11/08/2017
<b>Revision</b>	2
<b>SDS number</b>	11324
<b>SDS status</b>	Approved.
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.