

## SAFETY DATA SHEET

### 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also  
SWIMMING POOL PAINT

**Product number** 425/G149/2, 1916 + Dark Colours

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Aztec Chemicals Ltd  
Unit 16  
Orion Park  
Crewe  
CW1 6NG

+44(0)1270 655500(T)  
+44(0)1270 655501(F)

**Contact person** Office-, 9.00 - 16.30 hrs Mon - Thurs, 9.00 - 15.00 hrs Fri, as above

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1270 655500 (9.00 - 16.30 hrs Mon - Thurs, 9.00 - 15.00 hrs Fri)

**SDS No.** 10730

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** STOT SE 3 - H335, H336

**Environmental hazards** Aquatic Chronic 2 - H411

**Classification (67/548/EEC or 1999/45/EC)** Xi;R37. N;R51/53. R10,R66,R67.

##### 2.2. Label elements

###### Pictogram



**Signal word**

Warning

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

<b>Hazard statements</b>	H226 Flammable liquid and vapour. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	HYDROCARBONS, C9, AROMATICS, HYDROCARBONS, C9-C11, <2% AROMATICS

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>HYDROCARBONS, C9, AROMATICS</b>	<b>30-60%</b>
CAS number: —	EC number: 918-668-5
	REACH registration number: 01-2119455851-35-xxxx
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
<b>Chlorinated polymer 20</b>	<b>10-30%</b>
CAS number: 9006-03-5	
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>HYDROCARBONS, C9-C11, &lt;2% AROMATICS</b>	<b>5-10%</b>
CAS number: —	EC number: 919-857-5
	REACH registration number: 01-2119463258-33-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. R10,R66,R67.

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

<b>Carbon Black</b>		<b>1-5%</b>
CAS number: 1333-86-4	EC number: 215-609-9	REACH registration number: 01-2119384822-32
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -	
<b>TOLUENE</b>		<b>&lt;1%</b>
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-0026
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	
<b>ETHANOL</b>		<b>&lt;1%</b>
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43-xxxx
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11	
<b>METHANOL</b>		<b>&lt;1%</b>
CAS number: 67-56-1	EC number: 200-659-6	
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 T;R23/24/25,R39/23/24/25	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Get medical attention immediately. Do not induce vomiting.

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use solvents or thinners

**Eye contact** Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 10 minutes. Consult a physician for specific advice.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** Get medical attention promptly if symptoms occur after washing.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. Oxides of carbon. Oxides of nitrogen. Fire creates: Thermal decomposition or combustion products may include the following substances: Acid smoke or fumes. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

### Usage precautions

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Vapours may accumulate on the floor and in low-lying areas. Use explosion proof electric equipment. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Keep container tightly closed. Keep containers upright. Protect from light. Store in closed original container at temperatures between 5°C and 25°C. Store away from the following materials: Oxidising materials. Acids. Alkalis.

#### Storage class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m<sup>3</sup> vapour

##### Chlorinated polymer 20

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> total dust

##### Carbon Black

Long-term exposure limit (8-hour TWA): WEL 3,5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 7 mg/m<sup>3</sup>

##### TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

##### ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

##### METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 266 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 333 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### HYDROCARBONS, C9, AROMATICS

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 11 mg/kg/day Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Inhalation; Long term systemic effects: 32 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m <sup>3</sup>
<b>PNEC</b>	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

### Chlorinated Paraffin 48 (CAS: 63449-39-8)

<b>DNEL</b>	Industry - Inhalation; Long term systemic effects: 2.35 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 20 mg/kg/day Consumer - Oral; Long term systemic effects: 0.167 mg/kg/day Consumer - Dermal; Long term systemic effects: 8.3 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.003 mg/l - Marine water; 0.001 mg/l - STP; 60 mg/l - Sediment (Freshwater); 5710 mg/kg - Soil; 4640 mg/kg

### HYDROCARBONS, C9-C11, <2% AROMATICS

<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 300 mg/kg/day Industry - Inhalation; Long term systemic effects: 1500 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Inhalation; Long term systemic effects: 900 mg/m <sup>3</sup>
<b>PNEC</b>	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

### Carbon Black (CAS: 1333-86-4)

<b>DNEL</b>	Consumer - Inhalation; Long term systemic effects: 2 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 5 mg/l - Marine water; 5 mg/l

### TOLUENE (CAS: 108-88-3)

<b>DNEL</b>	Industry - Inhalation; Short term : 384 mg/m <sup>3</sup> Industry - Inhalation; Long term : 192 mg/m <sup>3</sup> Industry - Dermal; Long term : 384 mg/kg/day Consumer - Inhalation; Short term : 226 mg/m <sup>3</sup> Consumer - Inhalation; Long term : 56.5 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 8.13 mg/kg/day Consumer - Dermal; Long term : 226 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.68 mg/l - Sediment; 16.39 mg/l - Soil; 2.89 mg/l - STP; 13.61 mg/l

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

### ETHANOL (CAS: 64-17-5)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 950 mg/m <sup>3</sup> Workers - Inhalation; Short term local effects: 1900 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 343 mg/kg/day Consumer - Inhalation; Long term systemic effects: 114 mg/m <sup>3</sup> Consumer - Inhalation; Short term local effects: 950 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 206 mg/kg/day Consumer - Oral; Long term systemic effects: 87 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.96 mg/l - Marine water; 0.79 mg/l - Intermittent release; 2.75 mg/l - STP; 580 mg/l - Sediment (Freshwater); 3.6 mg/kg/day - Sediment (Marinewater); 2.9 mg/kg/day - Soil; 0.63 mg/kg/day

### METHANOL (CAS: 67-56-1)

<b>DNEL</b>	Workers - Dermal; Short term systemic effects: 40 mg/kg/day Workers - Inhalation; Short term systemic effects: 260 mg/m <sup>3</sup> Workers - Inhalation; Short term systemic effects: 40 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 40 mg/kg/day Workers - Inhalation; Long term systemic effects: 260 mg/m <sup>3</sup> Workers - Inhalation; Long term local effects: 260 mg/m <sup>3</sup> Consumer - Dermal; Short term systemic effects: 8 mg/kg/day Consumer - Inhalation; Short term systemic effects: 50 mg/m <sup>3</sup> Consumer - Oral; Short term systemic effects: 8 mg/kg/day Consumer - Inhalation; Long term local effects: 50 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 8 mg/kg/day Consumer - Inhalation; Long term systemic effects: 50 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 8 mg/kg/day Consumer - Inhalation; Short term local effects: 50 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 154 mg/l - Marine water; 15.4 mg/l - Sediment; 570.4 mg/kg - Soil; 23.5 mg/kg - STP; 100 mg/l - Intermittent release; 1540 mg/l

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Wear chemical splash goggles.

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

<b>Hand protection</b>	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.
<b>Hygiene measures</b>	Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.
<b>Respiratory protection</b>	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a full facepiece, supplied-air respirator.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid. Coloured liquid.
<b>Colour</b>	Black. Dark. Various colours
<b>Odour</b>	Organic solvents.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	Technically not feasible.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	40 approx. °C Closed cup.
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not determined.
<b>Upper/lower flammability or explosive limits</b>	: 0.8
<b>Other flammability</b>	Not determined.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	heavier than air
<b>Relative density</b>	1.00 - 1.10 @ @ 20 °C
<b>Solubility(ies)</b>	Insoluble in water
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	3.0 (ICI Rotothinner) P @ 25 °C
<b>Explosive properties</b>	Not determined.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not determined.



## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of 560 - 620 depending on colour g/litre.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not determined.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

#### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects** No data recorded.

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Inhalation** May cause respiratory system irritation. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. The product contains organic solvents. Overexposure may depress the central nervous system, causing dizziness and intoxication.

**Ingestion** Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea. May cause nausea, headache, dizziness and intoxication.

**Skin contact** May be absorbed through the skin. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema.

**Eye contact** Irritation of eyes and mucous membranes.

**Route of exposure** Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

#### Toxicological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

#### Acute toxicity - oral

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

<b>Acute toxicity oral (LD<sub>50</sub> mg/kg)</b>	3,492.0
<b>Species</b>	Rat
<b>Notes (oral LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE oral (mg/kg)</b>	3,492.0
<b><u>Acute toxicity - dermal</u></b>	
<b>Acute toxicity dermal (LD<sub>50</sub> mg/kg)</b>	3,160.0
<b>Species</b>	Rabbit
<b>Notes (dermal LD<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE dermal (mg/kg)</b>	3,160.0
<b><u>Acute toxicity - inhalation</u></b>	
<b>Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)</b>	6,193.0
<b>Species</b>	Rat
<b>Notes (inhalation LC<sub>50</sub>)</b>	Based on available data the classification criteria are not met.
<b>ATE inhalation (vapours mg/l)</b>	6,193.0
<b><u>Skin corrosion/irritation</u></b>	
<b>Animal data</b>	Repeated exposure may cause skin dryness or cracking.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Based on available data the classification criteria are not met.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	Based on available data the classification criteria are not met.
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Based on available data the classification criteria are not met.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Based on available data the classification criteria are not met.
<b>IARC carcinogenicity</b>	None of the ingredients are listed or exempt.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

<b>STOT - single exposure</b>	STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Target organs</b>	Respiratory system, lungs Central nervous system
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.
<b>General information</b>	
	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.
<b>Ingestion</b>	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking. Discoloration of the skin.
<b>Eye contact</b>	May cause temporary eye irritation.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target organs</b>	Central nervous system Respiratory system, lungs

### SECTION 12: Ecological Information

**Ecotoxicity** There are no data on the ecotoxicity of this product. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

#### 12.1. Toxicity

##### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

<b>Toxicity</b>	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
<b><u>Acute aquatic toxicity</u></b>	
<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 3.2 mg/l, Daphnia magna
<b>Acute toxicity - microorganisms</b>	EC <sub>50</sub> , 48 hours: 2.9 mg/l,

#### 12.2. Persistence and degradability

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

**Persistence and degradability** No data available.

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Persistence and degradability** The degradability of the product is not known.

**Biodegradation** - 78%: 28 days

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

#### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

### Ecological information on ingredients.

#### HYDROCARBONS, C9, AROMATICS

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Avoid the spillage or runoff entering drains, sewers or watercourses.

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

**Waste class** When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

#### 14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** Contains 1,2,4-Trimethylbenzene & White Spirit, Class 3, PG III, (38 °C c.c.) MARINE POLLUTANTS

**Proper shipping name (IMDG)** Contains 1,2,4-Trimethylbenzene & White Spirit, Class 3, PG III, (38 °C c.c.) MARINE POLLUTANTS

**Proper shipping name (ICAO)** Contains 1,2,4-Trimethylbenzene & White Spirit, Class 3, PG III, (38 °C c.c.) MARINE POLLUTANTS

**Proper shipping name (ADN)** Contains 1,2,4-Trimethylbenzene & White Spirit, Class 3, PG III, (38 °C c.c.) MARINE POLLUTANTS

#### 14.3. Transport hazard class(es)

ADR/RID class 1263

IMDG class 3

ICAO class/division 3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

#### 14.5. Environmental hazards

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-E, S-E  
Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>Revision comments</b>	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.
<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	19/07/2018
<b>Revision</b>	6.0
<b>Supersedes date</b>	11/05/2015
<b>SDS number</b>	10730
<b>SDS status</b>	Approved.

## 425/G149 - CHLORVAR CHLORINATED RUBBER BLACK + DARK COLOURS also SWIMMING POOL PAINT

**Risk phrases in full**

Not classified.  
R10 Flammable.  
R11 Highly flammable  
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.  
R37 Irritating to respiratory system.  
R38 Irritating to skin.  
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R63 Possible risk of harm to the unborn child.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

**Hazard statements in full**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H370 Causes damage to organs .  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**Signature**

Initials .....

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.