

## SAFETY DATA SHEET

### Post Office Black Gloss

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Post Office Black Gloss  
 APPLICATION Paint  
 SUPPLIER Aztec Chemicals  
 Gateway  
 Crewe  
 Cheshire  
 CW1 6YY  
 + 44 (0) 1270 655500 (T)  
 After hrs 0831300868  
 + 44 (0) 1270 655501 (F)

#### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
XYLENE	215-535-7	1330-20-7	30-60%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

#### 3 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation and in contact with skin. Irritating to skin.

CLASSIFICATION Xn;R20/21. Xi;R38. R10.

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Get medical attention if any discomfort continues. Do not give victim anything to drink if they are unconscious.

##### INHALATION

Provide rest, warmth and fresh air. Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing

##### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

##### SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use solvents or thinners as skin cleaning agents

##### EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire. Use water spray to cool containers.

##### SPECIAL FIRE FIGHTING PROCEDURES

Keep run-off water out of sewers and water sources. Dike for water control.

##### SPECIFIC HAZARDS

By fire, toxic gases may be formed (COx, NOx).

##### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

#### 6 ACCIDENTAL RELEASE MEASURES

##### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke, use naked flames or other sources of ignition. Provide adequate ventilation. Do not breathe vapour.

## Post Office Black Gloss

### ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### SPILL CLEAN UP METHODS

Collect with absorbent, non-combustible material into suitable containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Eliminate all sources of ignition. Avoid inhalation of vapours/spray and contact with skin and eyes. Static electricity and formation of sparks must be prevented.

### STORAGE PRECAUTIONS

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

### ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of spray.

### RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

### HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

### EYE PROTECTION

Use eye protection. Wear approved chemical safety goggles where eye exposure is reasonably probable.

### HYGIENE MEASURES

Wash hands after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

### PERSONAL PROTECTION

When using do not smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Black		
ODOUR	Aromatic.		
SOLUBILITY	Insoluble in water		
VAPOUR DENSITY (air=1)	>1	FLASH POINT (°C)	25 CC (Closed cup).

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### MATERIALS TO AVOID

Strong acids. Strong alkalies. Strong oxidising substances.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

Harmful by inhalation. Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

## Post Office Black Gloss

### INGESTION

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

### SKIN CONTACT

Repeated exposure may cause skin dryness or cracking. May cause skin irritation/eczema

### EYE CONTACT

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

### HEALTH WARNINGS

Irritating to skin.

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

### ROUTE OF ENTRY

Inhalation. Skin absorption.

### TARGET ORGANS

Central nervous system. Respiratory system, lungs.

### MEDICAL SYMPTOMS

Skin irritation. Vapours may cause drowsiness and dizziness.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	Paint		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	ADR LABEL NO.	3
RID CLASS NO.	3	RID PACK GROUP	III
UN NO. SEA	1263	IMDG CLASS	3
IMDG PAGE NO.	3372	EMS	3-05
MFAG	310, 313	MARINE POLLUTANT	No.
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	III		

## 15 REGULATORY INFORMATION

### LABELLING



Harmful

### CONTAINS

XYLENE

## Post Office Black Gloss

### RISK PHRASES

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.

### SAFETY PHRASES

S2	Keep out of the reach of children
S13	Keep away from food, drink and animal feeding stuffs.
S24	Avoid contact with skin.
S36/37	Wear suitable protective clothing and gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

### UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 1988. Chemicals (Hazard Information & Packaging) Regulations.

### EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC. System of specific information relating to Dangerous Preparations. 2001/58/EEC.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

### NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

## 16 OTHER INFORMATION

SDS NO. 10957

### SAFETY DATA SHEET STATUS

Approved.

DATE 27/06/2006

### RISK PHRASES IN FULL

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.