

SAFETY DATA SHEET

Sonic Bulk

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Sonic Bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint Stripper PC15 Non-metal surface treatment products Restricted to industrial use and to professionals approved in certain EU Member States — verify where use is allowed.
ADHESIVE REMOVER

1.3. Details of the supplier of the safety data sheet

Supplier Aztec Chemicals
Unit 16, University Way
Orion Park
Crewe
Cheshire
CW1 6NG
+ 44 (0) 1270 655500 (T)
+ 44 (0) 1270 655501 (F)
info@aztecchemicals.com

1.4. Emergency telephone number

Emergency telephone +44 (0)7831 300868

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 2 - H371 STOT SE 3 - H335, H336 STOT RE 2 - H373


Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xn;R20/21/22,R68/20/21/22. Carc. Cat. 3;R40.

Human health The product is irritating to eyes and skin. Contains a substance/a group of substances which may cause cancer. Central and/or peripheral nervous system damage. The liquid may be irritating to eyes, respiratory system and skin.

2.2. Label elements

Pictogram



Signal word

Warning

Sonic Bulk

Hazard statements	H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H371 May cause damage to organs . H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	P102 Keep out of reach of children. P260 Do not breathe vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective clothing, gloves, eye and face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P308+P313 IF exposed or concerned: Get medical advice/ attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with local regulations.
Supplemental label information	RCH002a Restricted to professional users.
Contains	DICHLOROMETHANE, METHANOL

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB. Danger of serious damage to health by prolonged exposure.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DICHLOROMETHANE		60-100%
CAS number: 75-09-2	EC number: 200-838-9	REACH registration number: 01-2119480404-41
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373	Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40	
METHANOL		5-10%
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01-2119433307-44
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC or 1999/45/EC) F;R11 T;R23/24/25,R39/23/24/25	

Sonic Bulk

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting. Remove affected person from source of contamination. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	May cause damage to mucous membranes in nose, throat, lungs and bronchial system.
Ingestion	There may be soreness and redness of the mouth and throat. Swallowing concentrated chemical may cause severe internal injury.
Skin contact	The product is irritating to eyes and skin. Prolonged contact may cause dryness of the skin. Blistering may occur.
Eye contact	The liquid is strongly irritating to eyes and skin. Corneal damage. Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Get medical attention immediately. Adrenaline and similar sympathomimetic drugs should be avoided following exposure as cardiac arrhythmia may result with possible subsequent cardiac arrest.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Water spray, fog or mist. Alcohol-resistant foam. Carbon dioxide (CO ₂). Dry chemicals, sand, dolomite etc. Use water spray to cool containers.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO ₂). Carbon monoxide (CO). Hydrogen chloride (HCl). Phosgene (COCl ₂). Thermal decomposition or combustion products may include the following substances: Very toxic or corrosive gases or vapours. May form explosive or toxic mixtures with air.
-------------------------	---

5.3. Advice for firefighters

Sonic Bulk

Protective actions during firefighting Avoid breathing fire gases or vapours. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. If risk of water pollution occurs, notify appropriate authorities.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with contaminated tools and objects. Clean contaminated objects and areas thoroughly, observing environmental regulations. Turn leaking containers leak-side up to prevent the escape of liquid. Do not breathe vapour/spray. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Bund storage facilities to prevent soil and water pollution in the event of spillage.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform authorities if large amounts are involved.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Use approved respirator if air contamination is above an acceptable level. Use explosion proof electric equipment. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Do not use in confined spaces without adequate ventilation and/or respirator. Avoid direct contact with the substance. Do not breathe vapour/spray. Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Static electricity and formation of sparks must be prevented. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame. Handle and open with care: pressure may occur if the container is stored in warm conditions. Contents may develop pressure upon prolonged storage. Keep away from food, drink and animal feeding stuffs.

Storage class Miscellaneous hazardous material storage.

Sonic Bulk

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DICHLOROMETHANE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 350 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 1060 mg/m³(Sk)

METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

DICHLOROMETHANE (CAS: 75-09-2)

DNEL	<p>Industry - Inhalation; Short term systemic effects: 353 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 2395 mg/kg/day</p> <p>Industry - Dermal; Long term local effects: 88.3 mg/m³</p> <p>Industry - Oral; Long term local effects: 0.06 mg/kg/day</p> <p>Consumer - Inhalation; Short term systemic effects: 706 mg/m³</p> <p>Consumer - Dermal; Long term systemic effects: 4750 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 353 mg/m³</p>
PNEC	<p>- Fresh water; 0.54 mg/l</p> <p>- Marine water; 0.194 mg/l</p> <p>- Intermittent release; 0.27 mg/l</p> <p>- Sediment (Freshwater); 4.47 mg/kg</p> <p>- Sediment (Marinewater); 1.61 mg/kg</p> <p>- Soil; 0.583 mg/kg</p> <p>- STP; 26 mg/l</p>

METHANOL (CAS: 67-56-1)

DNEL	<p>Industry - Dermal; Short term systemic effects: 40 mg/kg/day</p> <p>Industry - Inhalation; Short term systemic effects: 260 mg/m³</p> <p>Industry - Inhalation; Short term local effects: 260 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 40 mg/kg/day</p> <p>Industry - Inhalation; Long term systemic effects: 260 mg/m³</p> <p>Consumer - Inhalation; Long term local effects: 50 mg/m³</p> <p>Consumer - Dermal; Short term systemic effects: 8 mg/kg/day</p> <p>Consumer - Inhalation; Short term systemic effects: 50 mg/m³</p> <p>Consumer - Oral; Short term systemic effects: 8 mg/kg/day</p>
PNEC	<p>- Fresh water; 154 mg/l</p> <p>- Marine water; 15.4</p> <p>- Sediment; 570.4 mg/kg</p> <p>- Soil; 23.5 mg/kg</p> <p>- STP; 100 mg/l</p> <p>- Intermittent release; 1540 mg/kg</p>

Sonic Bulk

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

All handling should only take place in well-ventilated areas. Provide adequate general and local exhaust ventilation. This product must not be handled in a confined space without adequate ventilation. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Wear eye protection. Wear face protection.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a supplied-air respirator. Wear self-contained breathing apparatus.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Mobile liquid. Viscous liquid.
Colour	Milky.
Odour	Chlorinated hydrocarbons.
Initial boiling point and range	~40°C @
Flash point	None°C
Evaporation rate	<2% in 30 minutes
Vapour pressure	(dichloromethane) 380 mbar @ 20°C
Vapour density	(Dichloromethane) 2.93
Relative density	~1.22 @ 20°C
Solubility(ies)	~7 @ °C Slightly soluble in water. Soluble in the following materials: Organic solvents.
Viscosity	Brookfield ~3000 cPs @ 20°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 970 g/l.

Sonic Bulk

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended. Protect from moisture. Protect from sunlight.

10.2. Chemical stability

Stability Stable at normal ambient temperatures. Will decompose on red hot surfaces, in electric arcs or naked flames to evolve predominantly hydrochloric acid and a trace of phosgene gas.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Does not decompose when used and stored as recommended. May react with certain amines, e.g. polyurethane catalysts. Forms a detonable mixture with nitric acid.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with the following materials: Oxidising agents. Reducing agents. Acids. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames. Strong oxidising agents. Acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. Hydrogen chloride (HCl). Phosgene (COCl₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects IARC Int. Agency for Cancer Research. Consolidated carcinogen list. Carcinogen Category 3.

Acute toxicity - oral

ATE oral (mg/kg) 1,111.11

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 52.0

Species Rat

ATE inhalation (dusts/mists mg/l) 1.5

General information

Carcinogenicity: Chronic inhalation studies in mice have shown increases in lung and liver tumours, when exposed to concentrations of methylene chloride well in excess of the occupational exposure limit.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. May cause respiratory system irritation. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Ingestion

Swallowing concentrated chemical may cause severe internal injury. May cause liver and/or renal damage. Ingestion of large amounts may cause unconsciousness.

Sonic Bulk

Skin contact	Irritating to skin. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	Gas or vapour is harmful on prolonged exposure or in high concentrations. This product may cause skin and eye irritation. A single exposure may cause the following adverse effects: Central nervous system depression.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact
Target organs	Central nervous system Eyes Heart & cardiovascular system Kidneys Liver Respiratory system, lungs Skin
Medical symptoms	Severe irritation, burning and tearing. Dilated pupils. Severe skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes. Hypotension (low blood pressure).
Medical considerations	Skin disorders and allergies. Liver and/or kidney damage. Convulsions. Central nervous system depression. History of smoking.

Toxicological information on ingredients.

DICHLOROMETHANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 86.0

Species Rat

ATE inhalation (vapours mg/l) 86.0

METHANOL

Acute toxicity - oral

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 87.6

Species Rat

ATE inhalation (dusts/mists mg/l) 87.6

Carcinogenicity

Carcinogenicity NOAEL 1.3 mg/l, , Rat NOAEL 2.39 mg/l, , Monkey

Reproductive toxicity

Sonic Bulk

Reproductive toxicity - development - NOAEL: 1.33 mg/l, , Rat

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Toxicity Not available.

Acute toxicity - fish LC₅₀, 96 hours: 193-330 (dichloromethane) mg/l, Fish

Ecological information on ingredients.

DICHLOROMETHANE

Toxicity	Not available.
Acute toxicity - fish	LC ₅₀ , 96 hours: 193 mg/l, Pimephales promelas (Fat-head Minnow) LC ₅₀ , 96 hours: 220 mg/l, Lepomis macrochirus (Bluegill) LC ₅₀ , 96 hours: 97 mg/l, Marinewater fish LC ₅₀ , 96 hours: 193 mg/l, Freshwater fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 480 mg/l, Daphnia magna LC ₅₀ , 48 hours: 109 mg/l, Marinewater invertebrates LC ₅₀ , 48 hours: 27 mg/l, Freshwater invertebrates
Acute toxicity - aquatic plants	NOEC, 192 hours: 550 mg/l, Freshwater algae IC ₅₀ , 72 hours: >662 mg/l, Algae
Acute toxicity - microorganisms	EC ₈₀ , : 2590 mg/l, Activated sludge

METHANOL

Toxicity	Not available.
Acute toxicity - aquatic plants	EC ₅₀ , 48 hours: 1000 mg/l, EC ₅₀ , 96 hours: 22000 mg/l, LC ₅₀ , 48 hours: 10000 mg/l,

12.2. Persistence and degradability

Persistence and degradability The product is slowly degradable. The product is substantially removed in biological treatment processes.

Biodegradation Soil - DT₅₀ : 14.2 days

Ecological information on ingredients.

DICHLOROMETHANE

Persistence and degradability	Not available.
Phototransformation	Supplier's information. Calculated as, Air - DT ₅₀ : 79.3 days Photochemically oxidised in the troposphere.
Stability (hydrolysis)	Not hydrolysed under normal environmental conditions.

Sonic Bulk

Biodegradation - Half-life : 0.8 g/l, per hour

METHANOL

Persistence and degradability Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential BCF: 0.91 to 40 L/kg,

Ecological information on ingredients.

DICHLOROMETHANE

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product. BCF: < 100,

Partition coefficient log Kow: 1.25

METHANOL

Bioaccumulative potential Not available.

Partition coefficient log Pow: < 1

12.4. Mobility in soil

Mobility Readily absorbed into soil.

Ecological information on ingredients.

METHANOL

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

METHANOL

Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects

Other adverse effects Negligible ecotoxicity.

Ecological information on ingredients.

METHANOL

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sonic Bulk

General information	Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Larger quantities should be treated in a suitable plant or disposed of via a licensed waste disposal contractor.
Disposal methods	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

SECTION 14: Transport information

General Packs of 5L and under are not regulated under the Limited Quantities Provisions.

14.1. UN number

UN No. (ADR/RID)	2810
UN No. (IMDG)	2810
UN No. (ICAO)	2810

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	Toxic Liquid N>O>S (Contains dichloromethane & methanol)
Proper shipping name (IMDG)	Toxic Liquid N>O>S (Contains dichloromethane & methanol)
Proper shipping name (ICAO)	Toxic Liquid N>O>S (Contains dichloromethane & methanol)
Proper shipping name (ADN)	Toxic Liquid N>O>S (Contains dichloromethane & methanol)

14.3. Transport hazard class(es)

ADR/RID class	6.1 Toxic substances.
ADR/RID label	6.1
IMDG class	6.1
ICAO class/division	6.1

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-A, S-A
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Sonic Bulk

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. EU Decision number 455/2009/EC of the European Parliament and of the Council of 6th May 2009 (Amendment to Annex I to Directive 76/769/EEC) - Applicable to sales of dichloromethane within the European Union. Restricted to industrial use and to professionals approved in certain EU Member States — verify where use is allowed.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Revised classification.
Revision date	25/10/2016
Revision	1
SDS number	21154
SDS status	Approved.
Risk phrases in full	R10 Flammable. R11 Highly flammable. R20/21/22 Harmful by inhalation, in contact with skin and if swallowed. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R40 Limited evidence of a carcinogenic effect. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Sonic Bulk

Hazard statements in full

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H370 Causes damage to organs .
H371 May cause damage to organs .
H373 May cause damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.