

**SAFETY DATA SHEET****TEC 400****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product name** TEC 400**1.2. Relevant identified uses of the substance or mixture and uses advised against****Identified uses** Penetrating spray**1.3. Details of the supplier of the safety data sheet****Supplier** Aztec Chemicals  
Unit 16, University Way  
Orion Park  
Crewe  
Cheshire  
CW1 6NG  
+ 44 (0) 1270 655500 (T)  
+ 44 (0) 1270 655501 (F)  
info@aztecchemicals.com**1.4. Emergency telephone number****Emergency telephone** +44 (0)7831 300868**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification****Physical hazards**

Aerosol 1 - H222, H229

**Health hazards**

Not Classified

**Environmental hazards**

Aquatic Chronic 3 - H412

**Classification (67/548/EEC or 1999/45/EC)**

F+;R12. R52/53,R66.

**Human health**

Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Environmental**

This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

**Physicochemical**

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

**2.2. Label elements****Pictogram****Signal word**

Danger

**TEC 400****Hazard statements**

H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated  
 H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P102 Keep out of reach of children.  
 P501 Dispose of contents/container in accordance with local regulations.  
 P260 Do not breathe vapour/spray.  
 P271 Use only outdoors or in a well-ventilated area.

**Supplemental label information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards****SECTION 3: Composition/information on ingredients****3.2. Mixtures**

<b>Odourless Kerosene</b>	<b>30-60%</b>
CAS number: — EC number: 926-141-6 REACH registration number: 01-2119456620-43	
<b>Classification</b> Asp. Tox. 1 - H304	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. R66.
<b>PROPANE</b>	<b>30-60%</b>
CAS number: 74-98-6 EC number: 200-827-9 REACH registration number: Exempt under REACH	
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12
<b>BUTANE</b>	<b>10-30%</b>
CAS number: 106-97-8 EC number: 203-448-7 REACH registration number: Exempt under REACH	
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12
<b>ISOBUTANE</b>	<b>5-10%</b>
CAS number: 75-28-5 EC number: 200-857-2 REACH registration number: Exempt under REACH	
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12

**TEC 400**

<b>Cedarwood Oil (Virginian)</b> <span style="float: right;"><b>&lt;1%</b></span>	
CAS number: — EC number: — REACH registration number: N/A M factor (Acute) = 100 M factor (Chronic) = 100	
<b>Classification</b> Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. N;R50/53.
<b>Benzophenone</b> <span style="float: right;"><b>&lt;1%</b></span>	
CAS number: 119-61-9 EC number: 204-337-6 REACH registration number: 01-2119899704-20 M factor (Acute) = 100 M factor (Chronic) = 100	
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	<b>Classification (67/548/EEC or 1999/45/EC)</b> N;R50/53.
<b>MONOCYCLIC TERPENE</b> <span style="float: right;"><b>&lt;1%</b></span>	
CAS number: 5989-27-5 EC number: 227-813-5 REACH registration number: 01-2119529223-47 M factor (Acute) = 1 M factor (Chronic) = 1	
<b>Classification</b> Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. Xi;R38. N;R50/53. R10,R43.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Move affected person to fresh air at once.

**Inhalation**

If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

**Ingestion**

Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.

**Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water.

**Eye contact**

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

**4.3. Indication of any immediate medical attention and special treatment needed**

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

## TEC 400

### Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

### 5.2. Special hazards arising from the substance or mixture

#### Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

#### Protective actions during firefighting

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

---

## SECTION 6: Accidental release measures

---

### 6.1. Personal precautions, protective equipment and emergency procedures

#### Personal precautions

Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

### 6.2. Environmental precautions

#### Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3. Methods and material for containment and cleaning up

#### Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

### 6.4. Reference to other sections

---

## SECTION 7: Handling and storage

---

### 7.1. Precautions for safe handling

#### Usage precautions

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

### 7.3. Specific end use(s)

---

## SECTION 8: Exposure Controls/personal protection

---

### 8.1. Control parameters

#### Occupational exposure limits

## TEC 400

### Odourless Kerosene

Long-term exposure limit (8-hour TWA): OEL 1200 mg/m<sup>3</sup>

### PROPANE

Long-term exposure limit (8-hour TWA): SUP ppm

Short-term exposure limit (15-minute): SUP ppm

### BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm

Short-term exposure limit (15-minute): WEL 750 ppm

### ISOBUTANE

Long-term exposure limit (8-hour TWA): WEL 800 ppm

Short-term exposure limit (15-minute): WEL No std.

### MONOCYCLIC TERPENE

Long-term exposure limit (8-hour TWA): No std.

OEL = Occupational Exposure Limit.

WEL = Workplace Exposure Limit

### Ingredient comments

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

### Personal protection

When using do not smoke.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

### Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

### Hygiene measures

Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

---

## SECTION 9: Physical and Chemical Properties

---

### 9.1. Information on basic physical and chemical properties

#### Appearance

Aerosol.

#### Odour

Organic solvents.

#### Flash point

<-40°C

#### Upper/lower flammability or explosive limits

**TEC 400**

Lower : 1.8% - Upper 9.5%

**Auto-ignition temperature**

410-580°C

**Comments**

Information given is applicable to the major ingredient.

**9.2. Other information****SECTION 10: Stability and reactivity****10.1. Reactivity****10.2. Chemical stability****Stability**

Avoid the following conditions: Heat, sparks, flames.

**10.3. Possibility of hazardous reactions****10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

**10.5. Incompatible materials****10.6. Hazardous decomposition products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****General information**

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Inhalation**

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

**Skin contact**

Repeated exposure may cause skin dryness or cracking.

**Eye contact**

Vapour or spray in the eyes may cause irritation and smarting.

**Acute and chronic health hazards**

Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

**Route of entry**

Inhalation

**Target organs**

Central nervous system Respiratory system, lungs

**Medical symptoms**

Skin irritation. Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

**SECTION 12: Ecological Information****Ecotoxicity**

This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

**12.1. Toxicity**

## TEC 400

**12.2. Persistence and degradability****12.3. Bioaccumulative potential****12.4. Mobility in soil****12.5. Results of PBT and vPvB assessment****12.6. Other adverse effects****SECTION 13: Disposal considerations****13.1. Waste treatment methods****General information**

Do not puncture or incinerate, even when empty.

**Disposal methods**

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

**SECTION 14: Transport information****General**

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

**14.1. UN number**

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

**14.2. UN proper shipping name**

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

**14.3. Transport hazard class(es)**

ADR/RID class	2.1
ADR/RID subsidiary risk	
ADR/RID label	2.1
IMDG class	2.1
IMDG subsidiary risk	
ICAO class/division	2.1
ICAO subsidiary risk	

**Transport labels****14.4. Packing group**

Not applicable.

**TEC 400**

ADR/RID packing group

IMDG packing group

ICAO packing group

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

No.

**14.6. Special precautions for user**

EmS F-D, S-U

Emergency Action Code

Hazard Identification Number  
(ADR/RID)

Tunnel restriction code (D)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code****SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

**EU legislation**

Commission Regulation (EU) No 453/2010 of 20 May 2010.

**Guidance**

Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

**15.2. Chemical safety assessment****SECTION 16: Other information**

Revision date 14/11/2014

Revision 1

SDS number 10838

SDS status Approved.

**Risk phrases in full**

R10 Flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

**Hazard statements in full**



### **TEC 400**

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H304 May be fatal if swallowed and enters airways.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### **Disclaimer**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.