# SAFETY DATA SHEET **TEXPEN**

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name **TEXPEN** 

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

### 1.3. Details of the supplier of the safety data sheet

Aztec Aerosols Supplier

> Gateway Crewe Cheshire CW1 6FA

T+44 (0) 1270 656380 F+44 (0) 1270 656381 info@aztecaerosols.com

### 1.4. Emergency telephone number

+44 (0)7831 300868

### **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xi;R37. N;R51/53. R10, R66, R67.

#### 2.2. Label elements

#### Labelling



Irritant



Dangerous for the environment

Risk Phrases

R10

Flammable.

R37

Irritating to respiratory system.

R51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R66

Repeated exposure may cause skin dryness or cracking.

R67

Vapours may cause drowsiness and dizziness.

Safety Phrases

S2

Keep out of the reach of children.

S29/56

Do not empty into drains, dispose of this material and its container at

hazardous or special waste collection point.

S37

Wear suitable gloves.

S46

If swallowed, seek medical advice immediately and show this container or

label.

sheets.

S51

Use only in well-ventilated areas.

S61

Avoid release to the environment. Refer to special instructions/safety data

S64

If swallowed, rinse mouth with water (only if the person is conscious).

### 2.3. Other hazards

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

2 / 7

SDS No. 11281

## **TEXPEN**

| 1,2,4-TRIMETHYLBENZENE        |                   |                             | 5-10%                          |
|-------------------------------|-------------------|-----------------------------|--------------------------------|
| CAS-No.: 95-63-6              | EC No.: 202-436-9 | Registra                    | ntion Number: 01-2119472135-42 |
| Classification (EC 1272/2008) |                   | Classification (67/548/EEC) |                                |
| Flam. Liq. 3 - H226           |                   | R10                         |                                |
| Acute Tox. 4 - H332           |                   | Xn;R20                      |                                |
| Skin Irrit. 2 - H315          |                   | Xi;R36/37/38                |                                |
| Eye Irrit. 2 - H319           |                   | N;R51/53                    |                                |
| STOT SE 3 - H335              |                   |                             |                                |
| Aquatic Chronic 2 - H411      |                   |                             |                                |

| AROMATIC HYDROCARBON          |                   |                             | 30-60%                                |
|-------------------------------|-------------------|-----------------------------|---------------------------------------|
| CAS-No.: 64742-95-6           | EC No.: 265-199-0 |                             | Registration Number: 01-2119486773-24 |
| Classification (EC 1272/2008) |                   | Classification (67/548/EEC) |                                       |
| Flam. Liq. 3 - H226           |                   | Xn;R65.                     |                                       |
| EUH066                        |                   | Xi;R37.                     |                                       |
| STOT SE 3 - H335, H336        |                   | N;R51/53.                   |                                       |
| Asp. Tox. 1 - H304            |                   | R10,R66,R67.                |                                       |
| Aquatic Chronic 2 - H411      |                   |                             |                                       |

| XYLENE                        |                   |                             | 1-5%                                  |
|-------------------------------|-------------------|-----------------------------|---------------------------------------|
| CAS-No.: 1330-20-7            | EC No.: 215-535-7 |                             | Registration Number: 01-2119488216-32 |
| Classification (EC 1272/2008) |                   | Classification (67/548/EEC) |                                       |
| Flam. Liq. 3 - H226           |                   | R10                         |                                       |
| Acute Tox. 4 - H312           |                   | Xn;R20/21                   |                                       |
| Acute Tox. 4 - H332           |                   | Xi;R38                      |                                       |
| Skin Irrit. 2 - H315          |                   |                             |                                       |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## **SECTION 4: FIRST AID MEASURES**

# 4.1. Description of first aid measures

### General information

Get medical attention if any discomfort continues. Do not give victim anything to drink if they are unconscious.

### Inhalation

Move into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing can take place.

# Ingestion

DO NOT induce vomiting. Get medical attention immediately.

#### Skin contact

Remove contaminated clothes and rinse skin thoroughly with water. Wash skin thoroughly with soap and water. DO NOT use solvents or thinners as skin cleaning agents

#### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

## 4.3. Indication of any immediate medical attention and special treatment needed

### **SECTION 5: FIREFIGHTING MEASURES**

# 5.1. Extinguishing media

### **TEXPEN**

#### Extinguishing media

Use: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals. Water spray, fog or mist. Do not use water as an extinguisher.

## 5.2. Special hazards arising from the substance or mixture

#### Unusual Fire & Explosion Hazards

Fire causes formation of toxic gases.

## Specific hazards

When heated and in case of fire, harmful vapours/gases may be formed.

### 5.3. Advice for firefighters

# Protective equipment for fire-fighters

Use air-supplied respirator during fire fighting. Wear full protective clothing.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

#### 6.4. Reference to other sections

# **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

Read and follow manufacturer's recommendations. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Avoid inhalation of vapours.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from: Acids. Alkalis. Oxidising material.

## 7.3. Specific end use(s)

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

| Name                   | STD | TWA        | - 8 Hrs   | STEL    | - 15 Min  | Notes |
|------------------------|-----|------------|-----------|---------|-----------|-------|
| 1,2,4-TRIMETHYLBENZENE | WEL | 25 ppm     |           |         |           |       |
| AROMATIC HYDROCARBON   | SUP |            | 600 mg/m3 |         |           |       |
| XYLENE                 | WEL | 50 ppm(Sk) | 220       | 100     | 441       |       |
|                        |     |            | mg/m3(Sk) | ppm(Sk) | mg/m3(Sk) |       |

WEL = Workplace Exposure Limit.

### **Ingredient Comments**

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment





### **TEXPEN**

#### **Process conditions**

Provide eyewash station.

### **Engineering measures**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

#### Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

#### Hand protection

Use suitable protective gloves if risk of skin contact. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

#### Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

#### Hygiene measures

Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

#### Personal protection

When using do not smoke

#### Skin protection

Wear apron or protective clothing in case of contact.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.
Colour Various

Odour Organic solvents.

**Solubility** Negligible solubility in water.

Relative density >1.0 20

Flash point (°C) 42 CC (Closed cup).

9.2. Other information

Volatile Organic Compound (VOC) 351 g/litre

#### **SECTION 10: STABILITY AND REACTIVITY**

# 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

## 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

### 10.5. Incompatible materials

## Materials To Avoid

Strong oxidising substances. Strong acids.

# 10.6. Hazardous decomposition products

In case of fire, toxic gases (CO, CO2, NOx) may be formed.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

## Inhalation

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

#### Ingestion

May cause stomach pain or vomiting

### **TEXPEN**

#### Skin contact

Irritating to skin. Prolonged or repeated exposure may cause severe irritation.

### Eye contact

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

#### Route of entry

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

## **Target Organs**

Respiratory system, lungs Eyes Skin

### **Medical Symptoms**

Irritation of eyes and mucous membranes. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Ingestion may cause: Nausea, vomiting.

### **SECTION 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

### **12.1. Toxicity**

### 12.2. Persistence and degradability

## 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

## **SECTION 13: DISPOSAL CONSIDERATIONS**

# 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

## **SECTION 14: TRANSPORT INFORMATION**

**General** Packs of 5L and under are not regulated under the Limited Quantities Provisions.

#### 14.1. UN number

 UN No. (ADR/RID/ADN)
 1263

 UN No. (IMDG)
 1263

 UN No. (ICAO)
 1263

# 14.2. UN proper shipping name

Proper Shipping Name WHITE SPIRIT

# 14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3
IMDG Class 3
ICAO Class/Division 3

**Transport Labels** 

#### **TEXPEN**



### 14.4. Packing group

ADR/RID/ADN Packing group III
IMDG Packing group III
ICAO Packing group III

### 14.5. Environmental hazards

# **Environmentally Hazardous Substance/Marine Pollutant**

No.

### 14.6. Special precautions for user

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Uk Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

#### Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

## Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### **Guidance Notes**

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

#### **EU Legislation**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

### National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

### 15.2. Chemical Safety Assessment

## **SECTION 16: OTHER INFORMATION**

SDS No. 112841
Safety Data Sheet Status Approved.
Date 10.05.2013

#### Risk Phrases In Full

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R20 Harmful by inhalation.

R65 Harmful: may cause lung damage if swallowed.
R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

7 / 7

SDS No. 11281

## **TEXPEN**

### Hazard Statements In Full

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.
H335 May cause respiratory irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

H411 Toxic to aquatic life with long lasting effects.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.