

SAFETY DATA SHEET

Treadsafe

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Treadsafe

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier Aztec Chemicals
Unit 16, University Way
Orion Park
Crewe
Cheshire
CW1 6NG
+ 44 (0) 1270 655500 (T)
+ 44 (0) 1270 655501 (F)
info@aztecchemicals.com

1.4. Emergency telephone number

Emergency telephone +44 (0)7831 300868

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification

Physical hazards Flam. Liq. 3 - H226
Health hazards Elicitation - EUH208 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) R10,R52/53.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains Cobalt containing polymer. May produce an allergic reaction.

Treadsafe

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTER/doctor if you feel unwell.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P233 Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/container in accordance with local regulations.</p>
Supplemental label information	<p>EUH066 Repeated exposure may cause skin dryness or cracking.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Calcium Magnesium Carbonate 30-60% CAS number: 16389-88-1 EC number: 240-440-2
Classification Not Classified
Calcium Carbonate 5-10% CAS number: 1317-65-3 EC number: 215-279-6
Classification Not Classified
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 5-10% CAS number: — EC number: 919-857-5 REACH registration number: 01-2119463258-33-XXXX
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304

Treadsafe

White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics)			1-5%
CAS number: 64742-88-7	EC number: 919-446-0	REACH registration number: 01-2119458049-33	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		Xn;R65. N;R51/53. R10,R66,R67.	
Hydrocarbons, C9, aromatics			1-5%
CAS number: —	EC number: 918-668-5	REACH registration number: 01-2119455851-35-XXXX	
Classification			
Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
Organoclay			1-5%
CAS number: 68953-58-2	EC number: 273-219-4		
Classification			
Not Classified			
C.I. Pigment Yellow 74			1-5%
CAS number: 6358-31-2	EC number: 228-768-4	REACH registration number: 01-2119456819-22-XXXX	
Classification			
Not Classified			
Yellow Iron Oxide			1-5%
CAS number: 51274-00-1	EC number: 257-098-5	REACH registration number: 01-2119454754-33-XXXX	
Classification			
Not Classified			
Cobalt containing polymer			<1%
CAS number: —			
Classification			
Skin Sens. 1 - H317			

Treadsafe

Zirconium Propionate <1%		
CAS number: 84057-80-7	EC number: 281-897-8	REACH registration number: 01-2119978305-30-0000
Classification Not Classified		
2-ethylhexanoic acid, zirconium salt <1%		
CAS number: 22464-99-9	EC number: 245-018-1	REACH registration number: 01-2119979088-21-XXXX
Classification Repr. 2 - H361d		
METHANOL <1%		
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01-2119433307-44
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 STOT SE 1 - H370		Classification (67/548/EEC or 1999/45/EC) F;R11 T;R23/24/25,R39/23/24/25
ETHANOL <1%		
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319		Classification (67/548/EEC or 1999/45/EC) F;R11
XYLENE <1%		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304		Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20/21 Xi;R38

Treadsafe

2-METHYLPENTANE-2,4-DIOL		<1%
CAS number: 107-41-5	EC number: 203-489-0	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	Xi;R36/38	
Eye Irrit. 2 - H319		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	General first aid, rest, warmth and fresh air. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	Get medical attention if symptoms are severe or persist.
----------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO ₂). Dry chemicals. Water spray, fog or mist. Do not use water, if avoidable.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases or vapours. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. When heated and in case of fire, harmful vapours/gases may be formed.
Hazardous combustion products	Flammable Liquid Solvent vapours may form explosive mixtures with air.

5.3. Advice for firefighters

Protective actions during firefighting	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
Special protective equipment for firefighters	Cool containers exposed to flames with water until well after the fire is out. Do not allow runoff to sewer, waterway or ground.

Treadsafe

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Do not eat, drink or smoke when using this product. Avoid heat, flames and other sources of ignition. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Absorb spillage with non-combustible, absorbent material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12 as well.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Observe occupational exposure limits and minimize the risk of inhalation of vapours. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store separated from: Oxidising materials. Alkalis. Acids.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Calcium Magnesium Carbonate

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Calcium Carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Treadsafe

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics)

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

Hydrocarbons, C9, aromatics

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m³

Organoclay

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

C.I. Pigment Yellow 74

Long-term exposure limit (8-hour TWA): WEL 1.5 mg/m³ dust only

Yellow Iron Oxide

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ dust only

Zirconium Propionate

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 10 mg/m³

2-ethylhexanoic acid, zirconium salt

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 10 mg/m³

METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 266 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 333 mg/m³(Sk)

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

2-METHYLPENTANE-2,4-DIOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 25 ppm 123 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

DNEL

Consumer - Oral; Long term systemic effects: 300 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 300 mg/kg/day
 Industry - Dermal; Long term systemic effects: 300 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 1500 mg/m³
 Consumer - Inhalation; Long term systemic effects: 900 mg/m³

PNEC

Not available.
 This product is a UVCB substance and its composition will be variable, so reported properties may vary or require a range of values to describe them.

White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics (CAS: 64742-88-7)

Treadsafe

DNEL Industry - Inhalation; Short term systemic effects: 570 mg/m³
 Industry - Dermal; Long term systemic effects: 1056 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 1980 mg/m³
 Consumer - Inhalation; Short term systemic effects: 570 mg/m³
 Consumer - Dermal; Long term systemic effects: 1040 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 710 mg/m³
 Consumer - Oral; Long term systemic effects: 1040 mg/kg/day

Hydrocarbons, C9, aromatics

DNEL Consumer - Oral; Long term systemic effects: 11 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 11 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 32 mg/m³
 Industry - Dermal; Long term systemic effects: 25 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 100 mg/m³

Yellow Iron Oxide (CAS: 51274-00-1)

DNEL Industry - Inhalation; Long term systemic effects: 10 (inhalable) mg/m³
 Industry - Inhalation; Long term local effects: 10 mg/m³

ETHANOL (CAS: 64-17-5)

Ingredient comments WEL = Workplace Exposure Limits

DNEL Industry - Inhalation; Short term : 1900 mg/m³
 Industry - Dermal; Long term : 343 mg/kg/day
 Industry - Inhalation; Long term : 950 mg/m³
 Consumer - Inhalation; Short term : 950 mg/m³
 Consumer - Dermal; Long term : 206 mg/kg/day
 Consumer - Inhalation; Long term : 114 mg/m³
 Consumer - Oral; Long term : 87 mg/kg/day

PNEC - Fresh water; 0.96 mg/l
 - Marine water; 0.79 mg/l
 - Sediment; 3.6 mg/kg
 - Soil; 0.62 mg/kg
 - STP; 580 mg/l

METHANOL (CAS: 67-56-1)

DNEL Industry - Dermal; Short term systemic effects: 40 mg/kg/day
 Industry - Inhalation; Short term systemic effects: 260 mg/m³
 Industry - Inhalation; Short term local effects: 260 mg/m³
 Industry - Dermal; Long term systemic effects: 40 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 260 mg/m³
 Consumer - Inhalation; Long term local effects: 50 mg/m³
 Consumer - Dermal; Short term systemic effects: 8 mg/kg/day
 Consumer - Inhalation; Short term systemic effects: 50 mg/m³
 Consumer - Oral; Short term systemic effects: 8 mg/kg/day

Treadsafe

PNEC	<ul style="list-style-type: none"> - Fresh water; 154 mg/l - Marine water; 15.4 - Sediment; 570.4 mg/kg - Soil; 23.5 mg/kg - STP; 100 mg/l - Intermittent release; 1540 mg/kg
-------------	---

XYLENE (CAS: 1330-20-7)

DNEL	<p>Consumer - Oral; Long term systemic effects: 12.5 mg/kg/day</p> <p>Consumer - Dermal; Long term systemic effects: 1872 mg/kg/day</p> <p>Consumer - Inhalation; Long term systemic effects: 65.3 mg/m³</p> <p>Consumer - Inhalation; Short term : 260 mg/m³</p> <p>Industry - Dermal; Long term systemic effects: 3182 mg/kg/day</p> <p>Industry - Inhalation; Long term systemic effects: 221 mg/m³</p> <p>Industry - Inhalation; Short term : 442 mg/m³</p>
PNEC	<p>Not available.</p> <p>This product is a UVCB substance and its composition will be variable, so reported properties may vary or require a range of values to describe them.</p>

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Personal protection

When using do not smoke

Eye/face protection

Wear chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various
Odour	Organic solvents.

Treadsafe

Flash point	40°C CC (Closed cup).
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8%
Vapour density	> 1
Relative density	1.30 - 1.60 @ 20°C
Solubility(ies)	Insoluble in water.
Viscosity	6.0 - 8.0 P @ 25°C
9.2. Other information	
Volatility	40 - 45% Emits vapours if heated.
Volatile organic compound	This product contains a maximum VOC content of 350 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information	This product has low toxicity. Only large volumes may have adverse impact on human health.
Inhalation	Fire or high temperatures may form toxic and corrosive vapours. Gas or vapour may irritate the respiratory system.
Ingestion	Liquid irritates mucous membranes and may cause abdominal pain if swallowed.
Skin contact	Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.
Eye contact	May cause temporary eye irritation.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact
Target organs	Respiratory system, lungs Eyes Skin

Treadsafe

Medical symptoms	Irritation of eyes and mucous membranes. Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
Medical considerations	Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

SECTION 12: Ecological Information

Ecotoxicity	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
--------------------	--

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability	The product is not expected to be biodegradable.
--------------------------------------	--

12.3. Bioaccumulative potential

Bioaccumulative potential	The product contains potentially bioaccumulating substances.
----------------------------------	--

12.4. Mobility in soil

Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
---	---

12.6. Other adverse effects

Other adverse effects	The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.
------------------------------	---

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
-------------------------	---

Waste class	08 01 11 (solvent-based liquid waste)
--------------------	---------------------------------------

SECTION 14: Transport information

General	Packs of 5L and under are not regulated under the Limited Quantities Provisions.
----------------	--

14.1. UN number

UN No. (ADR/RID)	1263
-------------------------	------

UN No. (IMDG)	1263
----------------------	------

UN No. (ICAO)	1263
----------------------	------

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT PRODUCT CONTAINS WHITE SPIRITS
---------------------------------------	--------------------------------------

Proper shipping name (IMDG)	PAINT PRODUCT CONTAINS WHITE SPIRITS
------------------------------------	--------------------------------------

Proper shipping name (ICAO)	PAINT PRODUCT CONTAINS WHITE SPIRITS
------------------------------------	--------------------------------------

Treadsafe

Proper shipping name (ADN) PAINT PRODUCT CONTAINS WHITE SPIRITS

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID subsidiary risk

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk

ICAO class/division 3

ICAO subsidiary risk

Transport labels

14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS

Emergency Action Code

**Hazard Identification Number
(ADR/RID)**

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Dangerous Substances Directive 67/548/EEC.
Dangerous Preparations Directive 1999/45/EC.
System of specific information relating to Dangerous Preparations. 2001/58/EC.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.

Treadsafe

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	08/05/2015
Revision	1
SDS number	10629
SDS status	Approved.
Risk phrases in full	<p>R10 Flammable.</p> <p>R11 Highly flammable.</p> <p>R20 Harmful by inhalation.</p> <p>R20/21 Harmful by inhalation and in contact with skin.</p> <p>R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.</p> <p>R36/37/38 Irritating to eyes, respiratory system and skin.</p> <p>R36/38 Irritating to eyes and skin.</p> <p>R37 Irritating to respiratory system.</p> <p>R38 Irritating to skin.</p> <p>R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.</p> <p>R45 May cause cancer.</p> <p>R46 May cause heritable genetic damage.</p> <p>R48/23/24/25 Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>R66 Repeated exposure may cause skin dryness or cracking.</p> <p>R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	<p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H301 Toxic if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H311 Toxic in contact with skin.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H319 Causes serious eye irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H370 Causes damage to organs .</p> <p>H373 May cause damage to organs through prolonged or repeated exposure if inhaled.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>EUH208 Contains Cobalt containing polymer. May produce an allergic reaction.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.