

**SAFETY DATA SHEET**  
**White Gloss****1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

PRODUCT NAME White Gloss  
APPLICATION Paint  
SUPPLIER Aztec Chemicals  
Gateway  
Crewe  
Cheshire  
CW1 6YY  
+ 44 (0) 1270 655500 (T)  
After hrs 0831300868  
+ 44 (0) 1270 655501 (F)

**2 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
AROMATIC HYDROCARBON	265-199-0	64742-95-6	1-5%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
ETHYLBENZENE	202-849-4	100-41-4	5-10%	F;R11 Xn;R20
WHITE SPIRIT	265-185-4	64742-82-1	1-5%	Xn;R65. N;R51/53. R10,R66.
XYLENE	215-535-7	1330-20-7	30-60%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

**3 HAZARDS IDENTIFICATION**

Flammable. Irritating to skin. Harmful by inhalation and in contact with skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R20/21. Xi;R38. R10, R52/53.

**4 FIRST-AID MEASURES****GENERAL INFORMATION**

Do not give victim anything to drink if they are unconscious. Contact physician if discomfort continues.

**INHALATION**

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure breathing

**INGESTION**

DO NOT induce vomiting. Get medical attention immediately.

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use solvents or thinners as skin cleaning agents

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire. Use water spray to cool containers.

**SPECIAL FIRE FIGHTING PROCEDURES**

Keep run-off water out of sewers and water sources. Dike for water control.

**SPECIFIC HAZARDS**

By fire, toxic gases may be formed (COx, NOx).

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet. Do not smoke, use naked flames or other sources of ignition. Provide adequate ventilation. Do not breathe vapour.

## White Gloss

### ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### SPILL CLEAN UP METHODS

Collect with absorbent, non-combustible material into suitable containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Eliminate all sources of ignition. Avoid inhalation of vapours/spray and contact with skin and eyes. Static electricity and formation of sparks must be prevented.

### STORAGE PRECAUTIONS

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Protect from freezing and direct sunlight.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)
ETHYLBENZENE	WEL	100 ppm(Sk)	441 mg/m3(Sk)	125 ppm(Sk)	552 mg/m3(Sk)
AROMATIC HYDROCARBON	SUP		600 mg/m3		
WHITE SPIRIT	WEL		600 mg/m3		

### ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of spray.

### RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

### HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

### EYE PROTECTION

Use eye protection. Wear approved chemical safety goggles where eye exposure is reasonably probable.

### HYGIENE MEASURES

Wash hands after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

### PERSONAL PROTECTION

When using do not smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
ODOUR	Aromatic.		
RELATIVE DENSITY	0.89 - 1.20	VAPOUR DENSITY (air=1)	>1

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### MATERIALS TO AVOID

Strong acids. Strong alkalies. Strong oxidising substances.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

Harmful by inhalation. Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

### INGESTION

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

### SKIN CONTACT

Repeated exposure may cause skin dryness or cracking. May cause skin irritation/eczema

## White Gloss

### EYE CONTACT

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

### HEALTH WARNINGS

Irritating to skin.

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

### ROUTE OF ENTRY

Inhalation. Skin absorption.

### TARGET ORGANS

Central nervous system. Respiratory system, lungs.

### MEDICAL SYMPTOMS

Skin irritation. Vapours may cause drowsiness and dizziness.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	Paint		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	ADR LABEL NO.	3
RID CLASS NO.	3	RID PACK GROUP	III
UN NO. SEA	1263	IMDG CLASS	3
IMDG PAGE NO.	3372	EMS	3-05
MFAG	310, 313	MARINE POLLUTANT	No.
UN NO. AIR	1263	ICAO CLASS	3
AIR PACK GR.	III		

## 15 REGULATORY INFORMATION

### LABELLING



Harmful

### CONTAINS

XYLENE

### RISK PHRASES

R10	Flammable.
R38	Irritating to skin.
R20/21	Harmful by inhalation and in contact with skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### SAFETY PHRASES

S2	Keep out of the reach of children
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.

## White Gloss

S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S51	Use only in well-ventilated areas.
S24/25	Avoid contact with skin and eyes.
S36/37	Wear suitable protective clothing and gloves.
S56	Dispose of this material and its container to hazardous or special waste collection point.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

### UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 1988. Chemicals (Hazard Information & Packaging) Regulations.

### EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC. System of specific information relating to Dangerous Preparations. 2001/58/EEC.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

### NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

---

## 16 OTHER INFORMATION

---

SDS NO. 10715

### SAFETY DATA SHEET STATUS

Approved.

DATE 18/10/05

### RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.